



LIVE STREAMING MOTION DETECTION CAMERA SECURITY SYSTEM WITH EMAIL NOTIFICATION USING RASPBERRY PI

Angela Antony¹, Prof. G. R. Gidveer²

^{1,2}Dept. Electronics and Telecommunication

MGM's Jawaharlal Nehru Engineering College, Aurangabad, India

Email: angelaantony3@gmail.com¹, grgidveer@yahoo.com²

Abstract

In the present day scenario the security forms the most important part of our lives. Let it be in any form of life. Every one of us is in some way or the other bothered about the security of the house or the image or the near and dear ones. Now as the need for a very economic system has arise the solution has been found in a camera based security system based on the Raspberry Pi software that is extremely user friendly and cost effective. It is a credit card size computer that uses its own camera board for the security system. It is accompanied with a motion detection software that enables the camera to detect the motion and save the clicked image and immediately fwd to the portable devices for live streaming. For email notification a python script is used. With these components, a cost effective and efficient security camera system is made and reported here.

Keywords: Raspberry Pi, Motion Detecting, Email, Notifications, Python, Live Streaming.

I. INTRODUCTION

In this new era of technology the race is to provide a user friendly device which is cost effective. The capability of the device should be of such a nature that the cost of the item seems to be always less. Such a device is offered by Raspberry Pi systems. Its capability ranges from being a security system to a VPN server. Unlike other computers it has the capability to accept several program which includes "Python" language. Generally a security system will cost an approx of Rs 6000 to Rs 8000 where as the Raspberry Pi system will at max cost only Rs 4000. so who will be interested in buying a

security system of Rs 6000 (approx) where in one can get a system in a price range of Rs 2000 and with added features of email notification.

Apart from the price tag the next aspect is the user friendly nature of the system. As we are all aware that in India not everyone is a tech savvy individual. There by making it more important to ensure that the user does has to rewind the entire system to view the problem. In this system the email notification feature helps the user to see what is wrong than to see the entire video to find the error. The Raspberry Pi system is not only user friendly it also enables a individual wit medium knowledge to assemble the system if the necessary raw material is available and by creation of some extra files to support the operating system to store the data. So they are not only a money saving project but also a efficient security system.

II. PROPOSED SYSTEM

The proposed system has been designed to overcome the drawbacks of the previous security system and to improve the security, flexibility, efficiency whenever needed, having a security camera system may sometimes be impossible due to the exhaustive costs incurred during installation. The Raspberry Pi is a computer of a size of a credit card that has the capability to become a camera security system when its own camera board is used. It contains all the essential software to include motion detection which enables the Raspberry Pi's camera to detect motion and save the image as well as view a live streaming of the location from the camera. A python script, then directs the Raspberry Pi to send email notifications every time a motion is detected. With these components, a cost effective

and efficient security camera system is made as reported here. The proposed system block diagram is shown below.




Fig.1. Block diagram of Proposed system

1. **Component Description:**

The proposed system consists of following major components.

- 1.1 Raspberry Pi
- 1.2 LAN Cable
- 1.3 HDMI Display
- 1.4 PIR sensor
- 1.5 Buzzer
- 1.6 Keyboard and mouse
- 1.7 Webcam

2. **Raspberry Pi:**

An UK based company " Raspberry Pi Foundation" has developed a credit card sized single board computer which is called the Raspberry Pi System. The Raspberry Pi has a Broadcom BCM2835 System on a Chip (SoC), which includes an ARM1176JZF-S 700 MHz processor. It has an internal storage of 512 MB, external storage supported up to 32 GB, one Ethernet port, four-2.0 USB ports, one micro SD card slot, DSI display connector, one HDMI out port, one CSI Camera connector, 5V USB power, RCA video and audio jack as shown in the below figure.




Fig.2. Raspberry Pi B+ Model

3. The Raspberry Pi B+ model CPU is of ARM 11 family, operates at 700MHz. The GPU having Broadcom Video core-IV, open GLES 2.0, 1080p30, H.264/MPEG-4, AVC high profile decoder and capable of 1Gpixel/s, 1.5 G Texel/s (or) 24 GFLOPs of general-purpose (GPIO) compute. It operates 1mA at 5V power supply. With the help of GPIO pins we can control the devices sitting at home. The GPIO pin configuration is shown in below figure.

192.168.0.102:8000		3.3V		1	2	5.0V	
IN	GPIO 2	3	4	5.0V			
IN	GPIO 3	5	6	GROUND			
IN	GPIO 4	7	8	UART TX			
	GROUND	9	10	UART RX			
OUT	GPIO 17	11	12	GPIO 18		OUT	
OUT	GPIO 27	13	14	GROUND			
OUT	GPIO 22	15	16	GPIO 23		OUT	
	3.3V	17	18	GPIO 24		OUT	
OUT	GPIO 10	19	20	GROUND			
OUT	GPIO 9	21	22	GPIO 25		OUT	
OUT	GPIO 11	23	24	GPIO 8		OUT	
	GROUND	25	26	GPIO 7		OUT	

Fig.3. GPIO Header file of Raspberry Pi

The IN and OUT pins of the GPIO are mentioned, shows the current status of the appliances.8 GPIO pins for external peripheral connections supported by Raspberry Pi. 2- 3.3V, 2-5V pins for power supply connected to the external devices. With the Python is a default programming language for the Raspberry Pi with support of C, C++, Java, Perl and Ruby.

3.1 LAN Cable (Local Area Network):

To access the internet in Raspberry Pi we need LAN connection, with the help of which we can access the incoming and outgoing E-mail services. The LAN speed is much faster than the wireless connection.

3.2 HDMI Display:

To see the current status of the home appliances as well as the sensors (LPG gas, PIR, temperature) and also we will be able to check the updates regarding Raspberry Pi.

3.3 PIR sensor:

Passive Infrared sensor is to detect the motion of human being, as a human passes through this sensor, the temperature in the background will rise from room temperature to the body temperature and thus the motion or human will be detected.

3.4 Buzzer:

It has two wires. Namely red black. Polarity matters: black=ground Apply an oscillating voltage to make a noise. Oscillating voltage alternately squeezes and releases the piezo element. Must apply fluctuating voltage, a steady HIGH or LOW won't work. The buzzer case supports the piezo element and has resonant cavity for sound

3.5 Keyboard and mouse:

Key board and mouse are used to operate the Raspberry Pi, so we can easily do the programming and make changes easily.

3.6 Webcam:

A webcam is a mini video camera that has the capability to feed or stream its image in real time to, or through a computer to a computer network. When the image is "captured" by the computer, the video stream is saved, viewed or sent on to other networks via a system such as internet, and email as an attachment. When sent to a remote location, the video stream may be saved, viewed or sent there. Unlike an IP camera (which connects using Ethernet or Wi-Fi), a webcam is generally connected by a USB cable, or similar cable, or built into the computer hardware, such as laptops.

4 Interfacing:

- First of all need to install the Raspbian Operating system in the micro SD card, after that need to insert the SD card in Raspberry Pi kit and give the 5V power supply to the same.



Fig.4. Motion detecting camera security system experimental setup

- Connect the HDMI port to the LED TV and thus the display will be observed on LED screen.
- Now connect the keyboard and mouse to the Raspberry Pi USB ports, so will be able to write the code with the help of keyboard and mouse.
- Connect the LAN cable to Ethernet port and so we can access the Raspberry Pi and make the system interactive by sending and receiving E-mails.
- Need to write the code for the proposed system in Python language and store the results in the form of E-mail.
- LEDs are used to check the hardware setup before the interfacing and it will show either the device is in ON state or OFF state.

III. RESULTS

Case I:

When the email has been successfully sent, the LED and buzzer will 'OFF' and stop producing alarm sound respectively.




Fig.5. Email notification

Case II:

Figure 6 show the notification and content of the email received by the user respectively.




Fig.6. Content of the received email

Case III:

The main purpose of this android application was to enable the user to remotely control the activation of the system. 'Taken image' button is used to view the captured image once a motion is detected. Therefore the user can further confirm the reliability of the received image from the email.




Fig.7. Android application interface

Case IV:

The home surveillance system is then integrated with the Android application to develop an intelligent motion detecting camera

security system for home/offices. The complete Python program for the motion detecting camera security system. The system will only be activated when the user touches the 'Activate' button. Once the 'Activate' button is touched, the motion detecting camera security will performed their complete function. Otherwise, the user can deactivate the system by touching the 'Deactivate' button. Figure 6.7 shows the result obtained from the system integration.

```

pi@raspberrypi ~ $ sudo python system.py
Activate
GPIO pin 24 is HIGH
Image
Send Mail
GPIO pin 24 is LOW
Deactivate
Activate
GPIO pin 24 is HIGH
Image
Send Mail
GPIO pin 24 is LOW
    
```

Python program file

Activate' button is touched

Deactivate' button is touched

The system is activated again

Fig.8. Result of the system integration

IV. CONCLUSION

We have developed a comprehensive solution that can provides a user friendly home based automation and security application for all homes/offices. We accomplished this project through the integration of cheap, off-the-shelf, widely available devices, interfaces and software coupled with a user friendly interface. This work provides users with an easy to use mobile application for which they can remotely access and control their home appliances and security. In future we intend to provide a wireless relay connection and wireless sensors which can be movable and can be operated and which can be used in company and instates for Security to the whole building with one single system. This provides a full security support for homes.

REFERENCES

[1] Sharma, Rupam Kumar, et al. "Android interface based GSM home security system." Issues and Challenges in Intelligent Computing Techniques (ICICT), 2014 International Conference on. IEEE, 2014.

[2] De Luca, Gabriele, et al. "The use of NFC and Android technologies to enable a KNX-based smart home." Software, Telecommunications and Computer

- Networks (SoftCOM), 2013 21st International Conference on. IEEE, 2013.
- [3] Gu, Yi, et al. "Design and Implementation of UPnP-Based Surveillance Camera System for Home Security." Information Science and Applications (ICISA), 2013 International Conference on. IEEE, 2013.
- [4] Van Thanh Trung, Bui, and Nguyen Van Cuong. "Monitoring and controlling devices system by GPRS on FPGA platform." Advanced Technologies for Communications (ATC), 2013 International Conference on. IEEE, 2013.
- [5] Karia, Deepak, et al. "Performance analysis of ZigBee based Load Control and power monitoring system." Advances in Computing, Communications and Informatics (ICACCI), 2013 International Conference on. IEEE, 2013.
- [6] Ryu, Yeonghyeon, Jeakyu Yoo, and Youngroc Kim. "Cloud services based Mobile monitoring for Photovoltaic Systems." Cloud Computing Technology and Science (CloudCom), 2012 IEEE 4th International Conference on. IEEE, 2012.
- [7] Robson, Clyde, et al. "High performance web applications for secure system monitoring and control." Nuclear Science Symposium and Medical Imaging Conference (NSS/MIC), 2012 IEEE. IEEE, 2012.
- [8] Han, Jinsoo, et al. "User-friendly home automation based on 3D virtual world." Consumer Electronics, IEEE Transactions on 56.3 (2010): 1843-1847.
- [9] Xu, Lingshan, et al. "A Cloud-based monitoring framework for Smart Home." Cloud Computing Technology and Science (CloudCom), 2012 IEEE 4th International Conference on. IEEE, 2012.
- [10] Bajorek, Marcin, and Jędrzej Nowak. "The role of a mobile device in a home monitoring healthcare system." Computer Science and Information Systems (FedCSIS), 2011 Federated Conference on. IEEE, 2011.